


# SOLID Bifacial

Glass / Glass

60 Cell

Frameless




Self-cleaning  
effect




Salt mist  
resistance



Fire class A



Dust & Sand  
resistance



Ammonia  
resistance



Extreme load  
resistance



Positive sorting up to +5W

Front  
side

⚡ 350W

30

Product  
warranty

87%

Power  
guarantee

30

Efficiency  
guarantee

Electrical data (STC*)	
Maximum Power	350
Cell Technology	Bifacial
Open circuit voltage (V <sub>oc</sub> /V)	39,66
Short circuit Current (I <sub>sc</sub> /A)	11,01
Max Power Voltage (V <sub>mpp</sub> /V)	33,79
Max Power Current (I <sub>mpp</sub> /A)	10,37
Module Efficiency (η)	18,85%
Max System Voltage (V)	1500
Max Current (A)	20
Power Tolerance	0/+5W

\*Under Standard Test Conditions (STC) of irradiance of 1000W/sq. m., spectrum AM 1.5 and cell temperature of 25 °C Flash testing measurement accuracy of +/- 5% All transparency values are approximate +/- 3%



Additional power gain	5%	10%	20%	25%
Total Module Power (Wp)	367	385	420	437

Temperature ratings	
Current temperature coefficient (α)	+0,04% /° C
Voltage temperature coefficient (β)	-0,35% /° C
Power temperature coefficient (δ)	-0,47% /° C
Nominal Operating Module Temperature	46° C

Mechanical data	
Dimensions (LxWxH) (mm)	1770x1049x7,1mm
Dimensions with edge sealing (LxWxH) (mm)	1778x5x1057x5x7,1
Weight (kg)	30
Front / Back glass (mm)	3 mm
Cell Type	Bifacial
Cell Size (mm)	166x166
Busbars	9
Transparency %	10
Cell configuration	6x10
Frame	Frameless
Operating Temperature (°C)	-40 ÷ +85
Max Load (wind/snow) (Pa)	1600/5330**
Junction Box / IP Class	Split junction box / IP68
Cable Cross Section Size (mm2)	4
Cable length	1,2 m
Bypass Diodes	3
Connector	MC4 compatible

\*\*Safety factor 1,5

Dimensions & Mounting



Attention

- Always check if your system is compatible with local environmental conditions (wind/ snow load, temperatures) on your site to ensure safety and long-term energy production.
- Do not connect differently orientated PV panels in the same string / MPPT of the inverter (unless optimizers are used).
- Do not connect strings with an unequal amount of PV panels in one MPPT (unless optimizers are used).
- Use PV panels of same electrical parameters in one string/MPPT (unless optimizers are used).
- Always ensure that your inverter is equipped with DC disconnecter. If not it is recommended to install it externally.
- Never let different metals come in contact with each other. Use bi-metallic plates or plastic separators to eliminate galvanic corrosion.
- It is highly recommended to install SPD's in both AC and DC circuits because overvoltages void the warranty for inverters and also panels if they are harmed.
- It is highly recommended to ground PV panels mounting system and to install lightning protection in site.

Tips for Better Power Output

- Better module ventilation and shorter connection cables increase electrical energy production.
- Always observe object/mutual shading in site. Shading can drastically cut electrical energy generation output.
- Increase PV panel height from the ground so that more light can travel beneath the module and then reflect.
- The Albedo value increases significantly if modules are installed above white, lightreflecting surfaces.

