

# Growatt Smart EV Charger

THOR 11AS-S/P, THOR 22AS-S/P (Three Phase)

- Compatible with all branded EV
- Integration in existing & new-installed PV system
- Charge EV with 100% renewable energy by surplus solar power
- APP smart control & smart scheduling
- IP65 design for indoor or outdoor use



powering tomorrow  
**Growatt**

P O W E R  
- I N G  
T O M O -  
R R O W

[www.ginverter.com](http://www.ginverter.com)

Datasheet	THOR 11AS-P	THOR 11AS-S	THOR 22AS-P	THOR 22AS-S
<b>Input &amp; Output</b>				
Input voltage	400V AC			
Input frequency	50Hz			
Output voltage	400V AC			
Max. output power	11KW		22KW	
Max. output current	16A		32A	
Charging interface type	IEC 62196-2, Type 2			
Connection	Plug	Socket	Plug	Socket
Cable Length	5m	/	5m	/
<b>Protection</b>				
Over voltage protection	Yes			
Under voltage protection	Yes			
Over load protection	Yes			
Short circuit protection	Yes			
Earth leakage protection	Yes			
Over-temp protection	Yes			
Lightning protection	Yes			
<b>Function and Accessory</b>				
Ethernet/WIFI/4G	Yes/Yes/Opt			
LCD	Yes			
RCD	Type A + 6mA DC fault current protection (Equivalent to Type B)			
Charge activation	APP/RFID			
LED Indicator light	Yes			
Emergency stop button	Yes			
Multiple workmodes	Fast/ PV Linkage/ Off-peak/ Load balancing			
<b>General</b>				
Protection degree	IP65			
Environment temperature	-20°C ~ +65°C			
Relative humidity	5-95% non-condensing			
Maximum altitude	<2000m			
Cooling	Natural cooling			
Standby power consumption	<8W			
Dimension (W/H/D)	295/466/189mm			
Weight	12.5kg	10kg	12.5kg	10kg
Wall-mounting bracket/ Ground-mounting pole	Yes/Opt			
CE				