

# Wi-Fi Kit-20 and WiFi/LAN Kit-20

GoodWe's new generation of communication kits supports WiFi and WiFi + LAN connectivity, providing users with flexible options for configuration and operation. The integrated WiFi and LAN features ensure stable communication and faster response times. Additionally, the kits supports local configuration via Bluetooth, enhancing user convenience during setup and operation. With this advanced communication kits, data security during transmission is ensured, and the risk of data loss is minimized through support for breakpoint retransmission.



Enhanced Communication Stability



Remote Upgrade



Breakpoint Retransmission



Integrated Configuration

| Model                            |                           | WiFi/LAN Kit-20                                       | WiFi Kit-20        |
|----------------------------------|---------------------------|-------------------------------------------------------|--------------------|
| Input voltage (V)                |                           | 5                                                     |                    |
| Power Consumption (W)            |                           | ≤3                                                    |                    |
| Connection Interface             |                           | USB                                                   |                    |
| Communication                    | Ethernet Interface        | 10M / 100Mbps<br>Self-adaption                        | -                  |
|                                  | WLAN                      | IEEE 802.11 b / g / n @2.4 GHz                        |                    |
|                                  | Bluetooth                 | Bluetooth V4.2 BR / EDR<br>Bluetooth LE Specification |                    |
| Mechanical Parameters            | Dimensions (W × H × D mm) | 48.3 × 159.5 × 32.1                                   | 48.3 × 95.5 × 32.1 |
|                                  | Weight (g)                | 82                                                    | 54                 |
|                                  | Ingress Protection Rating | IP65                                                  |                    |
|                                  | Installation              | Plug and Play                                         |                    |
| Operating Temperature Range (°C) |                           | -30 ~ +60                                             |                    |
| Storage Temperature Range (°C)   |                           | -40 ~ +70                                             |                    |
| Relative Humidity                |                           | 0-95%                                                 |                    |
| Max. Operating Altitude (m)      |                           | 4000                                                  |                    |

\*: Please visit GoodWe website for the latest certificates.