

NEOSTAR

3P54 Mono-Glass Module

470W-500W

Technical Features:

-  Partial Shading Optimisation
-  Better Temperature Coefficient
-  High Temperature Restriction
-  Micro-crack Resistance
-  Higher Power
-  Lower BOS
-  More Aesthetic Values
-  Infinite Technology



red dot winner 2023



Product Warranty
Extendable to 25years*



Performance Warranty



Warranty partner

Munich RE 



500W
Output

25.0%
Efficiency

≤1%
First-year Degradation

≤0.35%
Annual Degradation from Year 2-30

30-year Linear Performance Warranty



Electrical Characteristics (STC: AM1.5 1000W/m² 25°C NOCT: AM1.5 800W/m² 20°C 1m/s)

Power Tolerance: 0~ + 3%

Module Type	AIKO-A470-MCE54Mw	AIKO-A475-MCE54Mw	AIKO-A480-MCE54Mw	AIKO-A485-MCE54Mw	AIKO-A490-MCE54Mw	AIKO-A495-MCE54Mw	AIKO-A500-MCE54Mw
Test Conditions	STC	NOCT	STC	NOCT	STC	NOCT	STC
P _{max} [W]	470	356	475	360	480	364	485
V _{oc} [V]	40.70	38.61	40.80	38.71	40.90	38.80	41.00
V _{mp} [V]	34.30	32.54	34.40	32.64	34.50	32.73	34.60
I _{sc} [A]	14.72	11.89	14.76	11.93	14.80	11.96	14.84
I _{mp} [A]	13.71	10.96	13.81	11.04	13.92	11.13	14.02
Module Efficiency	23.5%	23.8%	24.0%	24.3%	24.5%	24.8%	25.0%

Product Specification

Cell Type	N-Type ABC
Glass	3.2mm tempered glass
Backsheet	High weather resistant backsheet
Frame	Black anodized aluminum
Cable	4mm ² (IEC) 12AWG(UL) ±1200mm
No. of Cells	108(6*18)
Junction Box	IP68, 3 bypass diodes
Connector	Original MC4
Weight	21.1kg±3%
Dimension	1762*1134*30mm
Package Detail	37pcs per pallet / 222pcs per 20'GP / 962pcs per 40'HC

Temperature Ratings (STC)

Temperature Coefficient of I _{sc}	+ 0.05%/ °C
Temperature Coefficient of V _{oc}	- 0.22%/ °C
Temperature Coefficient of P _{max}	- 0.26%/ °C

Installation Guide

Operation Temperature	-40°C - +85°C
Maximum Series Fuse Rating	25A
Protection Class	Class II
Maximum System Voltage	DC1500V
Maximum Static Loading	Front 5400Pa Back 2400Pa
Hail Test	40 mm diameter hail at 23 m/s
Fire Rating	IEC Class C



www.aikosolar.com
marketing@aikosolar.com

*AIKO reserves right to update the specification without notice
*Optional Munich Re coverage is available upon request
V4.1_202509_DsDr_EN